

B SERIES

Model: **G35B**
 Radius: **5.5 to 15.2 m**
 Flow: **0.43 to 2.91 m³/hr; 7.2 to 48.5 l/min**

FEATURES

- Model: G35B: Full/Part Circle (50° - 360°)
- QuickCheck™ arc mechanism
- QuickSet-360 arc mechanism
- Nozzle choices:
 - 8 multi-trajectory 15°-25°
- Nozzle range:
 - #2 to #12
- Water lubricated gear-drive
- Check height up to 3 m in elevation change

OPERATING SPECIFICATIONS

- Radius: 5.5 to 15.2 m
- Flow: 0.43 to 2.91m³/hr; 7.2 to 48.5 l/min
- Pressure range: 2.8 to 4.5 bar; 280 to 450 kPa
- All B Series rotors are pressure rated at 10 bar; 1,000 kPa



G35B
 Pop-up height: 8 cm
 Overall height: 23 cm
 Flange diameter: 12 cm
 Female Inlet: 1/4" ACME

GOLF ROTORS

G35B - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Valve Options	3 Nozzle	4 Options*
G35 = Full/Part Circle 50° to 360°	B = Block rotor with check valve	6 = Installed G35 Nozzle* * Available in SSU model only SSU = #6 Includes nozzle rack	S = SSU* * Standard Stocking Unit

Example:
 G35 - B - 6 - S = G35 full/part circle block rotor, installed #6 nozzle with nozzle rack, standard stocking unit model

G835 NOZZLE PERFORMANCE DATA*							
Nozzle	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲
2 ● Yellow	2.8	280	5.5	0.43	7.2	14.3	16.6
	3.4	340	6.1	0.48	7.9	12.8	14.8
	4.1	410	6.7	0.55	9.1	12.1	14.0
	4.5	450	7.0	0.59	9.8	12.0	13.9
3 ● Yellow	2.8	280	7.0	0.68	11.4	13.9	16.0
	3.4	340	7.6	0.73	21.1	12.5	14.5
	4.1	410	8.2	0.80	13.2	11.7	13.6
	4.5	450	8.5	0.82	13.6	11.2	13.0
4 ● Yellow	2.8	280	7.6	0.89	14.8	15.3	17.6
	3.4	340	8.5	0.93	15.5	12.8	14.8
	4.1	410	9.1	1.00	16.7	12.0	13.8
	4.5	450	9.4	1.04	17.4	11.7	13.5
5 ● Yellow	2.8	280	8.8	1.07	17.8	13.7	15.8
	3.4	340	9.8	1.14	18.9	11.9	13.8
	4.1	410	10.1	1.20	20.1	11.9	13.7
	4.5	450	10.7	1.23	20.4	10.8	12.4
6 ● Yellow	2.8	280	9.8	1.36	22.7	14.3	16.5
	3.4	340	10.7	1.43	23.8	12.6	14.5
	4.1	410	11.3	1.50	25.0	11.8	13.6
	4.5	450	11.9	1.54	25.7	10.9	12.6
8 ● Yellow	2.8	280	11.0	1.77	29.5	14.7	17.0
	3.4	340	11.9	1.82	30.3	12.9	14.8
	4.1	410	12.8	1.89	31.4	11.5	13.3
	4.5	450	13.1	1.93	32.2	11.2	13.0
10 ● Yellow	2.8	280	11.9	2.20	36.7	15.6	18.0
	3.4	340	13.1	2.29	38.2	13.4	15.4
	4.1	410	13.7	2.34	39.0	12.4	14.4
	4.5	450	14.3	2.39	39.7	11.6	13.4
12 ● Yellow	2.8	280	13.4	2.73	45.4	15.2	17.5
	3.4	340	14.3	2.77	46.2	13.5	15.6
	4.1	410	14.6	2.84	47.3	13.3	15.3
	4.5	450	15.2	2.91	48.5	12.5	14.5

G835 NOZZLES



HQ5LRC Quick Coupler

with HSJ-1 SnapLok™ equipped swing joint



Introducing Hunter's new full line of HSJ heavy-duty swing joints with configurations for every need and every project. There is even a version specifically designed for quick coupler applications. The SnapLok outlet on HSJ-1 models come equipped with accommodations for both rebar and pipe stabilisation, as well as heavy-duty brass outlet threads with a unique anti-rotation locking feature.

See the new HSJ swing joints on page 173

* Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral. To calculate precipitation rates for 180° operation, multiply by 2.

ROTOR ACCESSORIES

HOSE-SWIVEL ADAPTERS

Models

- Hose swivel adapter for G90 and G900 Series (fits ¾" & 1" hose) P/N G90HS100
- Hose swivel adapter for G800 Series (fits ¾" & 1" hose) P/N G800HS100



Hose Swivel Adapters

RUBBER COVER KITS

Models

- G990 rubber cover kit (date codes 06/11 & prior only) P/N 473800
- G995 rubber cover kit (also G990 date codes 07/11 & after) P/N 473900



Rubber Cover Kit