

POINT SOURCE EMITTERS

Flow: 2, 4, 8, 15, 23 l/hr

FEATURES

- Slowly delivers water right to the plant
- Available in three convenient styles
- Pressure compensating from 1.0 to 3.5 bar; 100 to 350 kPa
- Flow labeled in imperial and metric units
- Assembled in the USA
- Optional diffuser cap available
- Barb emitters can be inserted into 1/2" and 1/4" tubing without tools for fast installation
- Colour-coded inlet: Models are colour-coded by flow rate for fast identification
- Coined edge for easy installation: Ribbed edges provide easy tool-free installation
- Array of flow rates: With flow rates ranging from 2.0 to 23.0 l/hr, plants can get the right amount of water from a single emitter

OPERATING SPECIFICATIONS

- Pressure compensating 1.0 to 3.5 bar; 100 to 350 kPa

POINT SOURCE EMITTERS - SPECIFICATION BUILDER: ORDER 1+ 2 + 3 + 4

1	Model	2	Flow Rate	3	Inlet	4	Qty./Bag
HE		2, 4, 8, 15, 23 l/hr		B = Self-piercing Barb	25/100		
				T = 10/32 Threaded	25/100		
HEB		4, 8 l/hr		1/2" Female Thread	25		
HE		Diff = Diffuser/Bug Cap		Snap Fit	50		

EMITTER MODEL CHART

	Model	Inlet Type	Flow (l/hr)
	Blue HE-050-B	Self-piercing Barb	2.0
	Black HE-10-B	Self-piercing Barb	4.0
	Red HE-20-B	Self-piercing Barb	8.0
	Tan HE-40-B	Self-piercing Barb	15.0
	Orange HE-60-B	Self-piercing Barb	23.0
	Blue HE-050-T	10/32" Thread	2.0
	Black HE-10-T	10/32" Thread	4.0
	Red HE-20-T	10/32" Thread	8.0
	Tan HE-40-T	10/32" Thread	15.0
	Orange HE-60-T	10/32" Thread	23.0
	Black HEB-10	1/2" Female Thread	4.0
	Red HEB-20	1/2" Female Thread	8.0

Point Source Emitters



Diffuser Cap

Gently distributes water at higher flows and protects the emitter outlet from clogging.



MICRO