

# PRO-SPRAY®

Models: **Shrub, 5 cm, 7.5 cm, 10 cm, 15 cm, 30 cm**  
 Inlet: 1/2"

## FEATURES

- Models: Shrub, 5 cm, 7.5 cm, 10 cm, 15 cm, 30 cm
- Compatible with all female threaded nozzles
- No side inlet (NSI) version available in 15 cm and 30 cm
- Innovative directional flush plug
- Warranty period: 5 years
- ▶ Co-molded wiper seal
- ▶ Heavy-duty spring
- ▶ Industry's strongest spray body
- ▶ Innovative seal design
- ▶ Pro-Spray check valve

## OPERATING SPECIFICATIONS

- Operational pressure range: 1.0 to 7.0 bar; 100 to 700 kPa

## FACTORY INSTALLED OPTIONS

- Drain check valve (up to 3 m of elevation)
- Reclaimed water ID cap

## USER INSTALLED OPTIONS

- Drain check valve (up to 3 m of elevation; P/N 437400)
- Reclaimed water ID cap (P/N 458520)
- Snap-on reclaimed cover (P/N PROSRCCAP)
- ▶ = *Advanced Feature descriptions on page 56*



### Pro-Spray Reclaimed

Pro-Spray models include optional factory-installed purple reclaimed caps.

SPRAYS



**PROS-00**  
 Retracted height: 4 cm  
 Inlet size: 1/2"



**PROS-02**  
 Retracted height: 10 cm  
 Pop-up height: 5 cm  
 Exposed diameter: 5.7 cm  
 Inlet size: 1/2"



**PROS-03**  
 Retracted height: 12.5 cm  
 Pop-up height: 7.5 cm  
 Exposed diameter: 5.7 cm  
 Inlet size: 1/2"



**PROS-04**  
 Retracted height: 15.5 cm  
 Pop-up height: 10 cm  
 Exposed diameter: 5.7 cm  
 Inlet size: 1/2"



[A] **PROS-06**  
 [B] **PROS-06-NSI**  
 Retracted height: 22.5 cm  
 Pop-up height: 15 cm  
 Exposed diameter: 5.7 cm  
 Inlet size: 1/2"



[A] **PROS-12**  
 [B] **PROS-12-NSI**  
 Retracted height: 41 cm  
 Pop-up height: 30 cm  
 Exposed diameter: 5.7 cm  
 Inlet size: 1/2"



PRO-SPRAY – SPECIFICATION BUILDER: ORDER 1 + 2	
1 Model	2 Options
<b>PROS-00</b> = Shrub Adapter	<b>(blank)</b> = No option
<b>PROS-02</b> = 5 cm Pop-up	<b>CV</b> = Factory-installed drain check valve ( <i>Pop-up models only</i> ) 15 cm and 30 cm models ordered
<b>PROS-03</b> = 7.5 cm Pop-up	<b>R</b> = Factory-installed reclaimed body cap ( <i>shrub molded in purple</i> )
<b>PROS-04</b> = 10 cm Pop-up	
<b>PROS-06</b> = 15 cm Pop-up	
<b>PROS-06-NSI</b> = 15 cm Pop-up (no side inlet)	
<b>PROS-12</b> = 30 cm Pop-up	
<b>PROS-12-NSI</b> = 30 cm Pop-up (no side inlet)	

### Examples:

- PROS-04** = 10 cm Pop-up
- PROS-06 - CV** = 15 cm Pop-up, drain check valve
- PROS-12 - CV - R** = 30 cm Pop-up, drain check valve, reclaimed body cap