

SUPPLY TUBING

17 MM POLYETHYLENE PROFESSIONAL TUBING

Uses: **Water transportation**
Size: **OD 17.8 mm x ID 15.2 mm**

FEATURES

- 17.8 mm outside diameter x 15.2 mm inside diameter
- Connect using PLD-Loc fittings
- Made with linear low density UV-resistant polyethylene
- Thicker wall, commercial grade
- Warranty period: 2 years

OPERATING PRESSURE

- 0 to 4.1 bar; 0 to 410 kPa



17 mm PE Tubing

17 MM PE TUBING - SPECIFICATION BUILDER: ORDER 1 + 2 + 3

1 Model	2 Tubing Diameter	3 Length
TWPE = Thick-Walled Polyethylene Tubing	700 = 17.8 mm outside diameter	100 = 30 m
		250 = 76 m
		500 = 152 m
		1K = 305 m

Example:

TWPE-700 - 250 = 17 mm polyethylene tubing in a 76 m roll

DISTRIBUTION TUBING

6 MM POLYETHYLENE AND VINYL TUBING

Uses: **Water transportation**
Size: **OD 6.4 mm x ID 4.3 mm**

FEATURES

- 6.4 mm outside diameter x 4.3 mm inside diameter
- Connect using standard 6 mm fittings
- Offered in vinyl or polyethylene
- UV Resistant materials
- Polyethylene is better choice in warm climates
- Vinyl is more flexible and useful in cold climates
- Warranty: 2 years

OPERATING PRESSURE

- 0 to 4.1 bar; 0 to 410 kPa



6 mm Tubing

6 MM TUBING - SPECIFICATION BUILDER: ORDER 1 + 2 + 3

1 Model	2 Tubing Diameter	3 Length
HQPE = Polyethylene Tubing HQV = Vinyl Tubing	250 = 6.4 mm outside diameter	100 = 30 m
		250 = 76 m
		1K = 305 m

Example:

HQPE-250 - 1K = 6 mm polyethylene tubing in a 305 m roll

MICRO